



BLACK CORE, AQUA GUARD FARMHOUSE COLLECTION

GREENGUARD CERTIFICATION
Ensures that a product has met some of the worlds' most rigorous and comprehensive standards for low emissions of volatile organic compounds (VOCS) into indoor air.



FLOORSORE CERTIFICATION
Is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring materials, adhesives and underlayments.



SPECIFICATIONS

Construction	Carbon Core
Edge Type	Bevel
Overall Thickness	10
Wear Layer	AC4
Nominal Length	48
Nominal Width	7 1/4
Coverage	20.45
Pieces / Box	8
Install Method	Floating
IIC	67
STC	70

PRODUCT DIMENSIONS	OVERALL THICKNESS 10 mm
	7 1/4 nominal
PACKAGING (PER CARTON)	7 Planks
TOP LAYERS	Aqua Pro Water Resistant Flooring
	CORE Black Core - carbon core with resin
	DENSITY 1470 kg/m3 +/-10%
	1.5 mm padding
INSTALLATION	50 year residential 20 year commercial
UNDER-FLOOR HEATING	yes
STATIC LOAD	ASTM F970 2000 PSI
Heat Exposure Resistance F1700(70°C/6h) Swelling after submersion	ASTM F2199 <0.10% EN16511 NALFA LF 01-2011 0% Class 4, Heavy Commercial
Impact Insulation Class	ASTM E492-09 IIC Rating = 67
Castor Chair Resistance	ISO 4918 PASS
FIRE RATING	ASTM E648/ 662 CLASS 1
Wear Resistance	EN 13329 method A CLASS 34 COMMERCIAL
F1700	EN 16511 CLASS 34 HEAVY COMMERCIAL
LEAD	CPSIA NOT DETECTED
Substances of Very High Concern (SVHC)	(Mercury, Chromium VI, Cadmium, NOT DETECTED
Substances of Very High Concern (SVHC)	SCCP, Benzene, Xylene, T ributyltin, etc.)