





## Rigid Core Timeless Winter Collection

The Timeless Winter Collection Rigid Core SPC flooring is constructed with a high density thermo- plastic composite which is extremely stable and can be installed over most subfloors. Since there are no wood fibers, The Winter Collection is 100% Waterproof and can be wet mopped. 25 year residential and 5 year light commercial use.

|   |   |
|---|---|
| <p><b>GREENGUARD CERTIFICATION</b><br/>Ensures that a product has met some of the worlds' most rigorous and comprehensive standards for low emissions of volatile organic compounds (VOCS) into indoor air.</p> |  |
|---|---|

|   |   |
|---|---|
| <p><b>FLOORSCORE CERTIFICATION</b><br/>Is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring materials, adhesives and underlays.</p> |  |
|---|---|

### THE FLOORING WAREHOUSE Specifications

|                   |                                    |
|-------------------|------------------------------------|
| CONSTRUCTION      | Rigid Core Stone Polymer Composite |
| EDGE TYPE         | bevel                              |
| OVERALL THICKNESS | 5.5 mm                             |
| WEAR LAYER        | 20 mil                             |
| NOMINAL LENGTH    | 60'                                |
| NOMINAL WIDTH     | 9"                                 |
| COVERAGE          | 22.64 ft.                          |
| PIECES / BOX      | 14                                 |
| WEIGHT            | 40 lbs                             |
| INSTALL METHOD    | Floating                           |

|  |  |  |
|--|--|--|
| PRODUCT DIMENSIONS                         | OVERALL THICKNESS  | 5.5 MM (1.5 IXPE)  |
|  | WIDTH AND LENGTH   | 9 X 60   |
| PACKAGING (PER CARTON)                     |  | 14 Planks 22.64 Sq.Ft. 50 lbs.<br>HIGH DEFINITION DECOR FILM.<br>EIR   |
| TOP LAYERS                                 |  | Enhanced Polyurethane Coating<br>with Ceramic Bead                     |
|  |  | 20 MIL WEAR LAYER  |
| CONSTRUCTION                               | CORE   | 3.4mm Limestone<br>Composite:min.65% stone, 0%<br>wood Virgin Material |
|  | DENSITY  | 1470kg/m3 +/-10%   |
|  | PAD  | 1.5mm XPE pad attached   |
|  | BEVEL  | Micro bevel  |
| INSTALLATION                               | FLOATING GLUELESS CLICK  |  |
| UNDER-FLOOR HEATING                        |  | APPROVED   |
| WARRANTY                                   | 5 YEAR LIGHT COMMERCIAL  | 25 YEAR RESIDENTIAL  |
| TEST DATA                                  |  |  |
| STATIC LOAD                                | ASTM F970  | 2000 PSI   |
| Heat Exposure Resistance<br>F1700(70°C/6h) | ASTM F2199<br>EN16511  | <0.10%   |
| Swelling after submersion                  | NALFA LF 01-2011   | 0%<br><br>Class 4, Heavy Commercial                                    |
| Impact Insulation Class                    | ASTM E492-09   | IIC Rating 60  |
| Castor Chair Resistance                    | ISO 4918   | PASS   |
| FIRE RATING                                | ASTM E648/ 662   | CLASS 1  |
| Wear Resistance                            | EN 13329 method A  | CLASS 34 HEAVY COMMERCIAL  |
| F1700                                      | EN 16511   | CLASS 34 HEAVY COMMERCIAL  |
| LEAD                                       | CPSIA  | NOT DETECTED   |
| Substances of Very High Concern<br>(SVHC)  | (Mercury, Chromium VI, Cadmium,<br>SCCp, Benzene, Xylene, T<br>ributyltin, etc.) | NOT DETECTED   |