

WPC Sound Solution Underlayment

Specifications

Name: WPC Sound Solution

Color: Black

Type: Vapor Barrier + Sound Reduction

Construction: black EVA foam with

black PE film

Coverage: 200sqft

Thickness: 1.5mm

Weight per Roll: 13lbs

Subfloor Compatibility: All Types

Floor Compatibility: WPC + Rigid Core

Vinyl

Installation Method: Floating

Recommended Usage: Residential &

Light Commercial

STC (Sound Transmission Class): 67

IIC (Impact Insulation Class): 52

Density: 160kg/m₃

Roll Width: 8in.

Roll Height: 40in.

Country of Manufacture: China

This product, when properly installed and used under normal conditions, is warranted to remain resilient and functional for a period equal to the warranted life of the selected Eternity floor.

Sound Solution WPC underlayment reduces floor noise by providing excellent sound absorption properties. In addition to sound absorption, it also serves as a superb moisture barrier. This high-density foam is suitable for use with floating WPC + Rigid Core LVT floors.

Installation

Follow the Eternity Laminate Installation Guide for detailed instructions.

- 1. **Prepare the Subfloor**. Level, repair, and make sure it is free of debris
- 2. **Begin the first row.** Place the roll on the ground with the film side down (facing the subfloor).
 - Note: the overlap of film should be positioned toward the open room and the foam will face the wall.
- Measure and cut accordingly. The plank width will determine how many rows of flooring you will be able to install. When you reach 1ft away from the underlayment, stop and roll out a second row of underlayment.
- Begin the second row. Unroll, measure, and cut. Place the foam side over the top of the film overlap from the previous row. Butt the edges together to create a nice seam, do not overlap.
- 5. **Tape the Seams.** Use industrial tape to adhere the seams together to make a flat & even surface
- 6. **Finish.** Continue installation in sections by repeating the steps above.





No.: XMCCM161201819-2.1

Date: Jan.05, 2017

Page: 1 of 5

Sample Name 1.5MM HIGH QUALITY EVA ACOUSTIC FOAM

Sample Info. OYT-1.5

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Test Required Selected test(s) as requested by applicant

Date of Receipt Dec.20, 2016 **Testing Start Date** Dec.20, 2016 **Testing End Date** Jan.04, 2017

Test result(s) For further details, please refer to the following page(s)

(Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested)

********[']To be continued*******

Signed for SGS-CSTC Standards Technical Services Co., Ltd. XM Branch

Civi Huang

Authorized Signatory





No.: XMCCM161201819-2.1

Date: Jan.05, 2017

Page: 2 of 5

Test Conducted:

Refer to ASTM E492-09(2016)^{ε1} Standard Test Method for Laboratory Measurement of Impact Sound Transmission Through Floor-Ceiling Assemblies Using the Tapping Machine ASTM E989-06(2012) Standard Classification for Determination of Impact Insulation Class (IIC)

Test Condition:

Sample Description : 1.5MM HIGH QUALITY EVA ACOUSTIC FOAM

Total thickness:1.5mm, surface density: about 0.22kg/m²

Project description : No decoration of sample surface, sample installation was assembled directly.

The test specimen was covered on a 140mm concrete floor with a drop ceiling,

testing area 11.3m², the drop ceiling construction showed in appendix2 Drop ceiling: 238mm cavity,50mm glass wool,12mm gypsum board

Test method : Two adjacent rooms, one the source room directly above the other the receiving

room. A standard tapping machine is placed in operation on the flooring system in source room. The average spectrum of the sound pressure levels produced

by the tapping machine is measured in the receiving room.

Test Equipment : RTA840 system

Test Environment : Source room volume 125m³, receiving room volume 100m³,

air temperature 18.4°C, air humidity 24.8%

Test Result

Test Item	Test Standard	Result	
Determination of Impact Sound Insulation Class	ASTM E492-09(2016) ^{£1} ASTM E989-06(2012)	IIC = 52	

******* To be continued******






No.: XMCCM161201819-2.1

Date: Jan.05, 2017

Page: 3 of 5

Appendix 1:				
f	Ln			
Hz	dB			
100	51.6			
125	53.8			
160	54.9			
200	52.8			
250	50.1			
315	47.1			
400	46.6			
500	44.8			
630	45.4			
800	45.4			
1000	40.1			
1250	43.4			
1600	41.5			
2000	43.8			
2500	47.0			
3150	47.1			
4000	42.7			
IIC	52			



Remark: L_n as the weighted normalized impact sound pressure level ****** To be continued******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention; attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponent to print the surface of the company. Any unauthorized attention, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing / inspection report & certificate, passes contact us at telephone: (86-755) 8307 1443, or amalit CN Doccheck@sgs.com




No.: XMCCM161201819-2.1


Date: Jan.05, 2017

Page: 4 of 5

Appendix 2: The constructional drawing of the floor/ceiling assembly system



Schematic diagram:



Note: The above test was carried out by an external laboratory assessed as competent. ******* To be continued*****



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein, Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to list Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alterion, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law, Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 6307 1443, or email: CN.Doccheck@sgs.com



No.: XMCCM161201819-2.1

Date: Jan.05, 2017

Page: 5 of 5

Photo Appendix:



SGS authenticate the photo on original report only ******End of report*****





No.: XMCCM161201819-2.2

Date: Jan.04, 2017

Page: 1 of 5

1.5MM HIGH QUALITY EVA ACOUSTIC FOAM Sample Name

Sample Info. OYT-1.5

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Test Required Selected test(s) as requested by applicant

Date of Receipt Dec.20, 2016 Testing Start Date Dec.20, 2016 **Testing End Date** Jan. 04, 2017

Test result(s) For further details, please refer to the following page(s)

(Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested)

********[']To be continued*******

Signed for SGS-CSTC Standards Technical Services Co., Ltd. XM Branch

-Civi Huang **Authorized Signatory**



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification is used softmed therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sgs.com

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn



No.: XMCCM161201819-2.2

Date: Jan.04, 2017

Page: 2 of 5

Test Conducted:

Refer to ASTM E90-09 Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements

ASTM E413-16 Classification for Rating Sound Insulation

Test Condition:

Sample Description 1.5MM HIGH QUALITY EVA ACOUSTIC FOAM

Total thickness:1.5mm, surface density: about 0.22kg/m²

Project description No decoration of sample surface, sample installation was assembled directly.

The test specimen was covered on a 140mm concrete floor with a drop ceiling,

testing area 11.3m², the drop ceiling construction showed in appendix2 Drop ceiling: 238mm cavity,50mm glass wool,12mm gypsum board

Test method Two adjacent rooms, one the source room directly above the other the receiving

> room. Taken the only significant sound transmission path between rooms is by way of the test partition. An approximately diffuse sound field is produced in the source room. Sound incident on the test partition causes it to vibrate and create

a sound field in the receiving room.

Test Equipment RTA840 system

Source room volume 125m³, receiving room volume 100m³, Test Environment

air temperature 18.4°C, air humidity 24.8%

Test Result

10011100411				
Test Item	Test Standard	Result		
Airborne sound transmission loss test and class	ASTM E90-09 ASTM E413-16	STC = 67		

****** To be continued******






No.: XMCCM161201819-2.2

Date: Jan.04, 2017

Page: 3 of 5

Appendix 1.

Appendix 1:			
f	TL		
Hz	dB		
100	46.4		
125	45.2		
160	48.5		
200	51.4		
250	56.3		
315	61.5		
400	64.9		
500	65.4		
630	66.3		
	00.0		
800	68.8		
1000	75.3		
1250	75.4		
1600	76.8		
2000	75.0		
2500	69.8		
3150	68.9		
4000	69.1		
5000	70.7		
STC	67		



Remark: TL is the transmission loss

****** To be continued******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's olde responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307

18/31 Yearon Power (1997) 18/31 Yearo

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn




No.: XMCCM161201819-2.2


Date: Jan.04, 2017

Page: 4 of 5

Appendix 2: The constructional drawing of the floor/ceiling assembly system



Schematic diagram:



Note: The above test was carried out by an external laboratory assessed as competent. ******* To be continued******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification is addition issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 | (86-592) 5765857 | f (86-592) 5765380 | www.sgsgroup.com.cn



No.: XMCCM161201819-2.2

Date: Jan.04, 2017

Page: 5 of 5

Photo Appendix:



SGS authenticate the photo on original report only ******End of report*****

